Real-Time and Deep-Time Detection of Quantum Foam Anomalies in Quantum Random Number Generator Outputs

Douglas C. Youvan

doug@youvan.com

April 28, 2025

Quantum Random Number Generators (QRNGs) have traditionally been deployed to ensure the generation of secure, unbiased random bitstreams essential for cryptography, secure communications, and scientific modeling. Relying on fundamental quantum phenomena such as photon detection or vacuum fluctuations, QRNGs have been rigorously tested against statistical standards like the NIST SP 800-22 suite to verify their operational integrity. However, a new frontier of opportunity exists: using QRNGs as sensitive probes to detect rare and subtle deviations from ideal randomness that could signal deeper physical processes, such as those hypothesized in quantum foam models or dynamical Casimir effects. Traditional randomness tests, optimized for gross statistical failures, are insufficient for capturing such elusive signatures. This paper introduces a dual-timescale monitoring framework, combining real-time lightweight statistical tests for immediate operational protection with deep-time exhaustive analyses aimed at uncovering hidden structures within the bitstream. Through this approach, QRNGs can serve not only their classical role in security but also emerge as scientific instruments capable of probing fundamental features of spacetime at its most granular scales.

Keywords: Quantum Random Number Generator, QRNG, quantum foam, dynamical Casimir effect, Unruh radiation, randomness testing, real-time anomaly detection, deep-time analysis, statistical signal processing, entropy monitoring, quantum informational phase transitions, rare event detection, quantum cryptography, quantum noise analysis. A collaboration with GPT-4o. . A collaboration with GPT-4o. CC4.0.

Abstract

Quantum Random Number Generators (QRNGs) are traditionally deployed to ensure secure, unbiased randomness for cryptographic and computational applications. Their output is typically assessed using standard randomness tests such as those specified in NIST SP 800-22, which focus on uniformity, independence, and the absence of detectable patterns. However, as QRNG technology matures, a new opportunity emerges: using QRNGs as sensitive probes into rare external disturbances and subtle quantum phenomena, such as those potentially arising from the structure of quantum foam or effects like the Dynamical Casimir Effect and Unruh radiation.

This paper presents the design of a dual-timescale detection system capable of addressing both operational integrity and scientific anomaly detection. The proposed framework combines real-time lightweight analysis with deep-time exhaustive analysis. Real-time monitoring employs sliding window statistical tests, lightweight versions of standard randomness checks, and trip detection based on deviations from expected stochastic behavior. Events are categorized by rarity, logged, and visualized in a continuous operational dashboard designed to capture immediate anomalies.

Parallel to the real-time layer, a deep-time analysis layer samples selected segments of QRNG output for intensive scrutiny. These samples undergo full NIST battery testing, entropy and compression-based analysis, spectral decomposition, autocorrelation studies, and fractal and nonlinear dynamic evaluations. This dual approach enables the system to maintain continuous operational protection while also creating a systematic archive for scientific study of rare or subtle disturbances in the QRNG output.

The outcome is a scalable and modular framework that serves both as an operational safeguard against traditional failures and as a scientific instrument for detecting potential deviations from pure quantum randomness. By combining immediate responsiveness with deep analytical capacity, the system is positioned to contribute both to the security of quantum technologies and to the exploration of foundational questions in quantum physics.

1. Introduction

Quantum Random Number Generators (QRNGs) represent a major advancement in the production of true randomness, leveraging fundamental quantum phenomena that are inherently unpredictable by any classical or deterministic process. Traditional random number generators, based on algorithmic or physical processes such as thermal noise, pseudo-random algorithms, or chaotic systems, can in principle be predicted or influenced by careful measurement or modeling. QRNGs, in contrast, draw upon phenomena such as photon detection, quantum tunneling, or vacuum fluctuations—processes whose outcomes, according to quantum mechanics, are fundamentally probabilistic and uncorrelated with prior states. As a result, QRNGs have found critical applications in cryptography, secure communications, authentication protocols, and scientific simulations requiring high-quality random input.

The traditional role of QRNGs has focused almost exclusively on operational security and system reliability. Devices are tested and certified based on their ability to produce bitstreams that pass rigorous statistical tests, such as those specified in the NIST SP 800-22 suite and related testing frameworks like Diehard or TestU01. These tests check for gross statistical properties including uniformity of 0s and 1s, independence between bits, expected distributions of runs, absence of predictable patterns, and spectral flatness. The goal is to ensure that QRNG outputs are indistinguishable from ideal random sequences for practical purposes, particularly in security-sensitive applications where predictability could be catastrophic.

However, an emerging opportunity exists beyond mere operational verification. QRNGs, by their very nature as detectors of microscopic quantum events, may also act as real-time probes into deeper physical phenomena, providing empirical access to the underlying structure of quantum spacetime itself. Theoretical constructs such as quantum foam—the hypothesized turbulence at the Planck scale caused by quantum fluctuations of spacetime—suggest that subtle, transient perturbations could exist beneath the threshold of current observational techniques. If such phenomena interact, even slightly, with the quantum systems

underpinning QRNGs, then rare or subtle deviations from pure randomness might manifest in the bitstreams, offering a new empirical window into foundational physics.

Realizing this opportunity presents significant challenges. Traditional randomness tests are insufficient for detecting the kinds of rare, localized, or structured deviations that would be expected from phenomena such as the Dynamical Casimir Effect, Unruh radiation, or spacetime foam interactions. Standard statistical batteries are optimized for detecting gross departures from randomness—such as biases, correlations, or compression in large datasets—not the fine-grained, low-probability anomalies that rare quantum effects would produce. An entirely new analytical approach is required, one capable of both reacting immediately to deviations and building up sensitivity over long timescales.

To meet these challenges, this paper proposes a dual-timescale monitoring architecture:

- The Real-Time Monitoring Layer focuses on operational health, employing lightweight statistical analyses to continuously detect gross anomalies, trends, and bursts of non-randomness as they emerge. Sliding window σ-deviation tracking, lightweight NIST tests, and real-time trip classification form the core of this layer.
- The Deep-Time Analysis Layer is designed for scientific exploration, selecting representative and anomalous data segments for exhaustive analysis. Full randomness test suites, entropy compression analysis, spectral decomposition, autocorrelation, fractal characterization, and nonlinear phase space methods are applied to search for rare, subtle, structured deviations that could reveal external quantum influences.

Together, these two layers form a monitoring system that is capable not only of maintaining the operational integrity of QRNGs but also of transforming them into active scientific instruments—instruments that could, for the first time, provide

direct empirical insights into the deepest, least understood features of the quantum world.

2. Standard Approaches to Randomness Verification

2.1 Traditional Methods

Verification of randomness in Quantum Random Number Generator (QRNG) outputs has traditionally focused on detecting gross statistical failures using well-established methods. These methods are designed to ensure that the bitstreams produced exhibit no discernible patterns, biases, or correlations that could compromise their intended use in security and computational applications.

A fundamental check involves bit balance, assessing whether the number of 0s and 1s across a sample of the bitstream conforms closely to the expected 50/50 distribution. Deviations from this balance, if statistically significant, could indicate bias in the generation mechanism, such as detector inefficiencies or systematic electronic noise.

Another essential metric is standard deviation monitoring, wherein the observed frequency of 0s and 1s, as well as other simple statistics like run lengths and transition rates, are compared to expected binomial or Gaussian distributions. Significant deviations—often expressed in units of standard deviation (σ)—trigger alarms or trip events, suggesting potential anomalies in the bitstream.

To formalize these checks, comprehensive statistical test suites have been developed and widely adopted. The NIST SP 800-22 test suite evaluates a variety of randomness properties, including frequency, block frequency, runs, long runs of ones, rank, spectral characteristics, and others. Complementary frameworks, such as the Diehard battery and more expansive packages like TestU01, provide additional layers of statistical testing rigor. These suites are designed to detect a wide range of possible departures from ideal randomness, ensuring operational integrity under typical conditions.

However, while effective for detecting gross failures, these traditional methods are inherently limited in their ability to identify rare, subtle, and structured anomalies that might arise from deeper physical effects influencing the QRNG output.

2.2 Motivation for Deeper Analysis: External Disturbance Possibilities

Beyond hardware malfunctions or environmental noise, QRNGs may, in principle, be sensitive to rare and subtle external quantum effects that could influence their outputs in ways not captured by standard statistical tests. Recognizing and detecting such disturbances requires a significant expansion of traditional verification strategies.

Two such potential sources of disturbance are of particular interest:

- Dynamical Casimir Effect: Under certain conditions, accelerating boundaries or fluctuating electromagnetic fields can create real photons from vacuum fluctuations. If such effects interact with the QRNG apparatus, they could inject unexpected photon events into the detection system, subtly biasing the bitstream.
- Unruh Effect: An observer undergoing acceleration perceives the vacuum as a thermal bath, effectively introducing a form of thermal noise. While extreme accelerations are typically required to produce detectable effects, even minuscule manifestations or related phenomena could cause slight but structured disturbances in QRNG outputs.

Traditional randomness verification methods are not designed to detect such rare and sporadic pollution. They primarily target persistent, gross failures, whereas phenomena like low-rate photon injections or thermal noise bursts would manifest as occasional, structured anomalies that may be statistically invisible over the broader bitstream.

Types of anomalies expected from such disturbances include:

- Low-rate photon injections, leading to bursty noise patterns that cause short-lived entropy reductions or clustering of identical bits.

- Thermal noise effects, resulting in slow bias drift or entropy fluctuations over long timescales.
- Temporal correlations, where the independence between successive bits is compromised, producing non-random timing patterns.

To detect these subtler forms of disturbance, additional tests beyond the standard suite are required. The following categories of tests are critical:

Test Type	Purpose
Standard randomness tests (NIST, Diehard)	Basic uniformity checks
Autocorrelation analysis	Detects time-correlated patterns across bits
Fourier spectral analysis	Reveals hidden periodicities in the bitstream
Sliding window entropy estimation	Monitors dynamic entropy stability over time
Bias drift monitoring	Detects slow systematic shifts in the 0/1 ratio
Burstiness detection	Identifies unexpected clusters of identical or correlated bits

These methods are designed to enhance the sensitivity of the QRNG monitoring system, ensuring that even rare, small-scale deviations from pure randomness—whether due to known quantum phenomena or unknown external influences—can be detected, analyzed, and, if necessary, acted upon.

In summary, detecting rare quantum disturbances requires a much more sensitive and structured monitoring framework than is provided by traditional randomness verification. A dual-layered system, combining fast operational checks with deep, scientific analysis, is essential for unlocking the full potential of QRNGs as both operational tools and scientific instruments.

---

3. Real-Time Monitoring Layer

3.1 Purpose

The primary purpose of the real-time monitoring layer is to maintain continuous operational oversight of the QRNG output stream and to enable rapid detection of anomalies that could compromise the integrity of the generated randomness. This layer is designed to respond to both operational failures—such as hardware malfunctions or environmental disturbances—and to the onset of subtle deviations that could indicate deeper, less understood physical phenomena.

The real-time monitoring system must operate at low computational overhead, ensuring it can analyze and visualize QRNG outputs without introducing significant latency, even at high bit rates. It must also provide a user interface that allows for immediate human recognition of anomalies and trends, supporting both automated response and expert review.

3.2 Methods

Sliding Window σ Deviation Tracking (EKG-Style Visualization)

A core component of the real-time layer is sliding window standard deviation (σ) tracking. Bitstreams are divided into overlapping or non-overlapping windows across multiple timescales (e.g., 1 second, 10 seconds, 100 seconds), and the statistical properties of each window are analyzed relative to the expected ideal random distribution.

Deviations from expectation are expressed in terms of standard deviations (σ), allowing the system to detect both small fluctuations and larger, more significant anomalies. The results are plotted in real time using EKG-style visualizations, with each timescale represented by a distinct trace. This dynamic, continuous display allows operators to rapidly recognize patterns such as growing instability, bias drift, or bursty disturbances.

Thresholds corresponding to different levels of deviation are pre-defined, typically at 2.4σ, 3σ, 4σ, and 5σ levels, to categorize events according to their rarity.

Lightweight NIST Subtests (Frequency, Runs, Approximate Entropy)

To supplement the sliding window analysis, a selection of lightweight randomness subtests drawn from the NIST SP 800-22 suite are applied continuously in real time. These tests include:

- Frequency (Monobit) Test: Verifies that the number of 0s and 1s remains balanced within statistical expectations.
- Runs Test: Assesses whether the distribution of consecutive runs of identical bits matches expected random behavior.
- Approximate Entropy Test: Measures the frequency of overlapping patterns to detect reductions in randomness.

These tests are chosen for their low computational overhead and their ability to provide immediate, meaningful assessments of the bitstream's statistical quality.

Trip Rarity Classification: Minor, Warning, Critical, Catastrophic

Detected deviations are classified according to their statistical severity:

- Minor Trip: Deviation crosses a 2.4σ threshold or results in a single lightweight test failure; likely benign but logged for trend analysis.
- Warning Trip: Deviation crosses a 3σ threshold or multiple lightweight tests fail simultaneously; indicates potential developing issues.
- Critical Trip: Deviation crosses a 4σ threshold or significant failure across key tests; suggests serious degradation requiring immediate attention.
- Catastrophic Trip: Deviation crosses 5σ or sustained multiple failures; signals probable hardware fault, external attack, or major quantum disturbance.

This stratified classification enables both automated systems and human operators to prioritize responses based on the assessed severity of anomalies.

3.3 Event Logging and Visualization

All detected trips are logged in real-time, creating a trip event history that captures:

- Timestamp of event occurrence,
- Window size and context,
- Magnitude of deviation or nature of test failure,
- Rarity classification.

Visualization components include:

- Trip Event Grids: Tabular or graphical displays showing the timing and severity of trips over recent intervals.
- Anomaly Rate Plots: Graphs illustrating the rate of minor, warning, critical, and catastrophic trips over time, enabling recognition of developing trends.
- Live Alerts: Real-time notifications (visual flashes, sounds, or system messages) when trip thresholds are crossed, with intensity scaled to event severity.

3.4 Real-Time System Dashboard Design

The real-time monitoring layer is intended for display on a dedicated high-resolution 4K monitor, allowing for clear and comprehensive visualization without information overload. The dashboard layout is organized into functional zones:

- Top half: EKG-style σ deviation traces for multiple timescales.
- Lower left: Real-time trip event log, scrolling continuously.
- Lower center: Meta-anomaly graphs, such as trip rate changes and bias drift trends.
- Lower right: System status indicators (green for normal, yellow for degraded, red for critical).

The high resolution allows all critical monitoring data to be presented simultaneously, maximizing operator situational awareness while preserving aesthetic and analytical clarity.

This real-time dashboard, when combined with a properly tuned trip detection and classification system, forms the first line of defense against both operational degradation and the early signatures of deeper quantum phenomena affecting QRNG outputs.

4. Deep-Time Analysis Layer

4.1 Purpose

While real-time monitoring focuses on immediate operational integrity and anomaly detection, the Deep-Time Analysis Layer is dedicated to exhaustive and detailed investigation of the QRNG output. This layer is specifically designed to detect rare, subtle anomalies that could easily evade real-time systems due to their small scale, infrequency, or complexity.

Deep-Time Analysis operates on selected chunks of the bitstream, applying computationally intensive tests that would be impractical to perform continuously. Through the careful accumulation and analysis of these samples, the Deep-Time layer seeks to identify deviations that could indicate external quantum disturbances, unrecognized system behaviors, or new physical phenomena, contributing both to system validation and to foundational scientific discovery.

4.2 Data Sampling Strategies

Because Deep-Time Analysis is computationally intensive, it is neither necessary nor practical to analyze every bit generated by the QRNG. Instead, effective sampling strategies are employed to select representative and potentially interesting subsets of the bitstream:

- Periodic Random Sampling: At fixed intervals (e.g., every 10 minutes), a random segment of the bitstream is selected for deep analysis. This ensures coverage across the operational timeline without bias, providing a baseline for long-term statistical characterization.
- Triggered Sampling After Clusters of Real-Time Anomalies: When the real-time layer detects clusters of trip events—especially warning, critical, or catastrophic classifications—the system flags nearby data segments for prioritized deep analysis. This event-driven sampling increases the likelihood of capturing meaningful anomalies when the system exhibits non-standard behavior.

The combination of random and triggered sampling maximizes the chances of detecting both spontaneous and externally induced anomalies without overwhelming computational resources.

4.3 Analytical Techniques

Once a data segment is selected, it undergoes a battery of sophisticated tests and analyses designed to probe deeper into the structure and randomness of the bitstream:

Full NIST SP 800-22 Suite

Unlike the lightweight subset used in real-time monitoring, the full NIST test suite is applied, including more computationally demanding tests such as:

- Block Frequency Test,
- Cumulative Sums Test,
- Random Excursions and Random Excursions Variant,
- Linear Complexity Test,
- Serial Test.

These tests evaluate more nuanced statistical properties, capable of detecting deeper deviations from randomness across multiple scales.

Compression-Based Entropy Analysis (e.g., Lempel-Ziv Complexity)

Compression-based tests measure the effective entropy of the bitstream by assessing its compressibility. Truly random sequences are largely incompressible, while sequences exhibiting structure, bias, or hidden periodicities can often be compressed. Techniques such as Lempel-Ziv complexity analysis provide sensitive measures of entropy loss, even when standard statistical tests pass.

Spectral Decomposition (FFT, Wavelet Transforms)

Spectral methods are employed to identify hidden periodic structures or frequency domain anomalies:

- Fast Fourier Transform (FFT) analysis detects dominant frequencies or repetitive structures that might arise from periodic external disturbances.
- Wavelet Transform analysis offers time-frequency localization, allowing detection of transient anomalies that do not persist long enough to dominate FFT spectra.

Fine-Scale Autocorrelation and Mutual Information Analysis

Detailed autocorrelation analysis evaluates dependencies between bits across a range of lags, searching for evidence of hidden temporal structure. Mutual information calculations extend this by detecting nonlinear dependencies between bits at different positions, providing a sensitive measure of subtle correlations that might not be visible through autocorrelation alone.

Fractal Dimension and Hurst Exponent Measurement

The bitstream is analyzed for fractal properties and scaling behavior:

- Hurst exponent estimation determines whether the sequence exhibits persistent, anti-persistent, or purely random behavior.
- Fractal dimension analysis assesses the complexity of the sequence's structure over different timescales.

Departures from the expected random walk behavior may indicate underlying structured processes or environmental influences.

Recurrence Quantification and Nonlinear Phase Space Analysis

Recurrence plots visualize when similar states recur within the system, offering a view into the underlying phase space structure of the bitstream dynamics. Recurrence Quantification Analysis (RQA) extracts statistical features from these plots, such as recurrence rate, determinism, and entropy of recurrence structures. Significant deviation from the expected "salt-and-pepper" random appearance may signal external perturbations or emergent structures within the random output.

4.4 Building a Historical Anomaly Map

Results from the Deep-Time analyses are not isolated but are accumulated over long timescales to build a historical anomaly map. This map records:

- Time and operational conditions of analyzed samples,
- Anomaly scores across different tests,
- Correlations between real-time events and deep-time anomalies.

Over weeks, months, and years, the historical anomaly map enables the identification of trends, cyclical behaviors, or persistent low-level deviations that

might indicate either gradual system degradation or deeper physical processes influencing the QRNG.

The long-term accumulation of such detailed analytical results transforms the QRNG system from a simple operational device into a sophisticated scientific instrument capable of contributing to the empirical study of quantum fluctuations and external quantum effects.

5. Bridging Real-Time and Deep-Time Layers

5.1 Interaction Between Layers

The Real-Time and Deep-Time layers are not designed to operate in isolation; rather, they form an interactive feedback system that enhances both operational monitoring and scientific discovery. Their interplay creates a dynamic, evolving system capable of adapting to changing conditions and learning from accumulated experience.

One critical point of interaction occurs when real-time trip patterns inform the selection of data segments for deep-time analysis. Specifically, the trip event logs generated by real-time monitoring—categorized by severity into minor, warning, critical, and catastrophic—are continuously scanned for clustering, recurrence, or escalation patterns. When clusters of higher-severity trips are detected, particularly those suggesting possible bursts of non-random behavior, the surrounding bitstream segments are automatically flagged for prioritized deep analysis. This approach ensures that the Deep-Time layer focuses its computationally expensive resources where anomalies are statistically more likely to occur, maximizing the likelihood of discovering meaningful deviations.

Conversely, findings from Deep-Time Analysis are used to inform and adjust the Real-Time layer's sensitivity thresholds. For example, if deep-time investigations reveal previously undetected long-range correlations, subtle bias drifts, or spectral anomalies that correspond to trip patterns initially categorized as "minor," the real-time system can be re-tuned to treat such trip patterns with higher urgency in

future monitoring. This dynamic adjustment prevents the system from becoming static or overly reliant on assumptions embedded during its initial configuration.

Thus, the interaction between real-time and deep-time layers establishes a learning feedback loop, enhancing both the immediate operational response and the long-term scientific sensitivity of the system.

5.2 Adaptive Monitoring Evolution

A key feature of the dual-timescale design is its ability to evolve adaptively over time. As more real-time and deep-time data is collected and analyzed, the system builds an increasingly detailed understanding of its own operational behavior and the nature of anomalies it encounters.

This adaptive evolution occurs through several mechanisms:

- Threshold Refinement: Sensitivity levels for σ-deviation trips, lightweight NIST test alarms, and other real-time metrics are periodically recalibrated based on long-term statistical observations. If certain patterns previously considered insignificant are consistently associated with deeper anomalies, their detection thresholds can be lowered appropriately.
- Anomaly Pattern Recognition: As trip logs and deep-time anomaly maps accumulate, machine learning algorithms or expert-driven statistical models can be applied to recognize recurring patterns or trends that indicate emerging issues or rare physical phenomena. These patterns can be incorporated into the real-time monitoring logic, improving early warning capabilities.
- Resource Allocation Optimization: Over time, the system can optimize how it allocates computational resources between real-time monitoring and deep-time analysis. For example, periods of operational stability may allow more aggressive deep-time exploration, while periods of elevated real-time anomaly rates may shift focus toward tighter operational vigilance.

- Discovery-Driven Updates: If Deep-Time Analysis identifies unexpected types of anomalies—such as evidence of exotic quantum phenomena, environmental couplings, or unknown systematics—the monitoring framework can be updated to specifically target these new discoveries in both real-time and deep-time operations.

By embedding adaptability at its core, the system transcends the static monitoring frameworks of traditional QRNG validation. It becomes a dynamic observatory, continuously tuning itself to both protect its operational role and push the boundaries of what can be learned from quantum randomness.

6. Implementation Strategy

The successful deployment of a dual-timescale QRNG monitoring system requires careful attention to the physical and computational constraints imposed by the bitstream rate, memory management, processing power, and system architecture. This section outlines a practical implementation framework that ensures both real-time responsiveness and the capacity for deep analytical exploration.

6.1 QRNG Data Rates

Typical commercially available and research-grade QRNGs operate at bit generation rates ranging from approximately 100 kilobits per second (kbps) to 1 megabit per second (Mbps). Some specialized or next-generation QRNGs can achieve rates significantly higher, but the 100 kbps to 1 Mbps range represents the most common operational envelope.

At 1 Mbps, the system would receive approximately 86 gigabits per day (or about 10.75 gigabytes per day). Thus, while the data volume is nontrivial, it remains well within the capabilities of modern dedicated computing hardware, particularly when employing intelligent buffering, real-time filtering, and selective deep storage strategies.

6.2 Real-Time Buffer Management for Sliding Window Analysis

For real-time monitoring, an efficient buffer management system must be implemented to handle sliding window analysis without causing processing delays or memory bottlenecks.

Key strategies include:

- Circular Buffers: In-memory circular buffers are employed to maintain fixed-size recent windows (e.g., 1-second, 10-second, 100-second buffers) that continuously overwrite old data as new bits arrive. This minimizes memory use while maintaining constant access to the most recent bitstreams for real-time analysis.
- Windowed Summaries: Instead of reanalyzing every bit from scratch, rolling summary statistics (e.g., running sums, counts, entropy estimates) are updated incrementally as new bits enter and old bits leave the window. This drastically reduces computational overhead.
- Asynchronous Processing Threads: Real-time analysis is managed by lightweight, high-priority threads or processes that operate independently from the background deep-time analysis, ensuring that critical real-time monitoring tasks are not interrupted by slower, heavier computations.

6.3 Resource Management

Because the system must simultaneously perform lightweight real-time analysis and occasional heavy deep-time analysis, effective resource management is critical.

The two computational pipelines are divided as follows:

- Lightweight Real-Time Pipeline:
    - Continuous sliding window σ deviation calculations.
    - Lightweight NIST subtests (Frequency, Runs, Approximate Entropy).

    - Real-time trip detection, classification, and logging.
    - EKG-style visualization and live anomaly rate plotting.

This pipeline prioritizes low-latency processing to guarantee immediate reaction to operational anomalies. Its design must ensure that analysis and visualization remain smooth and reliable even under high anomaly rates.

- Heavier Background Deep-Time Pipeline:
    - Full NIST SP 800-22 battery execution on selected samples.
    - Compression-based entropy and complexity measurements.
    - Fourier and wavelet spectral analysis.
    - Autocorrelation and mutual information scans.
    - Fractal and nonlinear dynamics evaluations.

This pipeline operates in parallel, at lower priority, drawing from stored sample buffers. Deep-Time processing tasks can be batch-queued and scheduled during periods of low system load, or distributed across multiple processing cores or servers if available.

Adaptive scheduling mechanisms ensure that background tasks do not interfere with real-time operations. In extreme cases of sustained high real-time anomaly rates, deep analysis jobs can be temporarily paused to preserve system responsiveness.

6.4 Modular and Scalable System Design

A crucial architectural principle is to build the QRNG monitoring system with modularity and scalability from the outset:

- Modular Software Architecture:
    - Functional components—such as real-time statistical monitoring, deep-time sampling and analysis, event logging, dashboard visualization, and alert systems—are implemented as independent modules with clearly defined interfaces.
    - New test algorithms, analytical methods, or visualization enhancements can be integrated without disrupting existing operations.
- Scalable Infrastructure:
    - The system is capable of scaling vertically (by upgrading hardware such as CPUs, GPUs, or memory) or horizontally (by distributing deep-time analysis tasks across multiple servers or cloud instances).
    - In a distributed deployment, real-time monitoring remains local and immediate, while deep-time analysis may be centralized or cloud-based, enabling aggregation of results from multiple QRNG sources.
- Future-Proofing Analytical Frameworks:
    - Analytical engines are designed with plug-in architectures, allowing seamless integration of future improvements such as advanced anomaly detection algorithms, machine learning-based pattern recognition, or more sophisticated statistical methods.
    - Thresholds, sampling strategies, and analysis parameters are user-configurable and dynamically adjustable based on ongoing system learning and operator feedback.

This modular, scalable design ensures that the QRNG monitoring system will not become obsolete as bit rates increase, as analytical techniques evolve, or as new scientific objectives emerge.

7. Discussion

7.1 Strengths of the Dual-Timescale Design

The dual-timescale architecture combining real-time monitoring with deep-time analysis offers significant advantages both for operational security and for scientific discovery.

First, the system provides immediate protection against attacks, hardware failures, and operational degradation. Through continuous sliding window monitoring, lightweight NIST subtests, and real-time trip detection, the system can rapidly identify deviations from ideal randomness. These deviations, whether caused by environmental factors, component malfunctions, or malicious interference, can be flagged and addressed promptly, preserving the reliability and trustworthiness of the QRNG output.

Second, beyond immediate operational needs, the system establishes a long-term scientific platform for detecting rare and subtle deviations from pure randomness that could signal deeper quantum structures. By systematically accumulating and analyzing carefully selected samples at high analytical depth, the system becomes capable of identifying anomalies that traditional tests would overlook. This dual-purpose design transforms the QRNG from a passive security device into an active experimental probe of quantum phenomena, potentially opening new empirical windows into quantum foam, vacuum fluctuations, or other exotic effects at the frontier of physics.

In short, the dual-timescale design not only meets the QRNG's traditional operational goals but expands its utility into the realm of scientific exploration, making it uniquely powerful compared to systems focused solely on one objective or the other.

7.2 Challenges

While the advantages of the dual-timescale approach are substantial, it also introduces several significant challenges that must be carefully managed.

One challenge is balancing sensitivity against computational load. Increasing the sensitivity of anomaly detection—by lowering trip thresholds, expanding the number of real-time statistical tests, or deepening the analytical intensity of deep-time studies—inevitably demands greater computational resources. Particularly at high bit rates, there is a risk that deep-time analysis could overwhelm system capabilities if not intelligently managed. Strategic sampling, adaptive scheduling, and modular resource allocation must be maintained to prevent resource contention between the real-time and deep-time layers.

Another challenge is avoiding overfitting anomalies, particularly in low-entropy or noisy windows. Random fluctuations in even perfectly random bitstreams can produce apparent short-term structure purely by chance. Over-interpreting such natural statistical noise could lead to false discoveries, wasted computational effort, or misdirected scientific inquiry. Therefore, statistical rigor, appropriate controls, and long-term trend analysis must be incorporated into both real-time and deep-time pipelines to distinguish meaningful signals from random noise.

Careful calibration of thresholds, use of appropriate p-value corrections, and statistical aggregation across many samples will be critical to ensuring that anomalies flagged by the system represent genuine deviations worth further investigation.

7.3 Broader Impacts

The broader impacts of deploying a system of this design could be significant across multiple domains.

In the field of quantum technology and cryptographic security, improving the reliability, sensitivity, and robustness of QRNGs enhances the trustworthiness of critical systems in government, finance, communications, and research sectors.

More ambitiously, in the realm of fundamental physics, the dual-timescale QRNG monitoring system could serve as a new class of experimental apparatus—a real-time quantum foam observatory. Detecting deviations from pure randomness on timescales and scales not previously accessible could provide empirical evidence for or against models of spacetime structure at the Planck scale, vacuum fluctuation dynamics, or emergent quantum phenomena not yet captured by standard quantum field theories.

Even null results—confirming the extraordinary stability and purity of QRNG outputs over long timescales and environmental conditions—would provide valuable constraints on speculative physics theories, informing both theoretical development and future experimental designs.

Ultimately, the system bridges the operational demands of engineering with the exploratory aspirations of science, fulfilling both practical and philosophical goals in the advancement of technology and knowledge.

8. Conclusion

This paper has presented a comprehensive framework for the dual-timescale monitoring of Quantum Random Number Generator (QRNG) outputs, designed to serve both operational security needs and the long-term pursuit of scientific discovery. By combining a Real-Time Monitoring Layer for immediate anomaly detection with a Deep-Time Analysis Layer for exhaustive study of rare and subtle deviations, the proposed system addresses both the practical and exploratory dimensions of QRNG deployment.

The Real-Time layer ensures that the QRNG output remains within expected operational parameters, rapidly detecting deviations caused by hardware faults, environmental disturbances, or malicious attacks. Through lightweight statistical tests, sliding window σ-deviation monitoring, and an intelligently structured event logging and visualization system, real-time monitoring provides a robust first line of defense without sacrificing responsiveness or efficiency.

The Deep-Time layer, operating in parallel, applies heavy analytical techniques to carefully selected samples of the bitstream. By leveraging full randomness test suites, entropy compression analysis, spectral and fractal analysis, and nonlinear phase space methods, this layer systematically explores the potential for subtle, structured anomalies—anomalies that could arise from rare external quantum disturbances such as the Dynamical Casimir Effect or Unruh radiation. Deep-Time analysis transforms the QRNG from a mere device for generating random numbers into a scientific instrument capable of probing the fundamental fabric of quantum reality.

Together, these two layers form a dynamic, interactive system that not only safeguards the operational reliability of quantum technologies but also opens a new empirical frontier for studying the nature of randomness and the possible structures underlying quantum spacetime.

Looking forward, several avenues for future work are envisioned:

- Scaling to Multiple QRNGs: Deploying the dual-timescale framework across multiple independent QRNG systems would enable cross-validation of anomaly detection events. Correlated anomalies across geographically separated systems could provide stronger evidence for global quantum disturbances, while isolated anomalies could be more confidently attributed to local environmental factors or hardware issues.
- Synchronized Global Observations: A network of globally distributed QRNGs operating under synchronized monitoring regimes could function as a large-scale observatory for quantum foam effects, gravitational disturbances, or other exotic phenomena. Temporal correlations across distant sites would offer unprecedented experimental power to test fundamental physics hypotheses.
- Automated Anomaly Classification Using Machine Learning: As historical anomaly data accumulates, machine learning models—particularly unsupervised clustering algorithms and anomaly detection neural networks—can be trained to classify types of deviations, distinguish

between random noise and meaningful patterns, and predict emerging behaviors. Incorporating such adaptive intelligence into the monitoring framework would further enhance its scientific sensitivity and operational robustness.

In conclusion, by reimagining the role of QRNGs from purely operational devices to hybrid operational-scientific instruments, and by engineering a system capable of both real-time vigilance and deep-time exploration, we lay the foundation for a new class of quantum technologies. These technologies serve not only the needs of cryptography and computation but also the timeless human pursuit of understanding the deepest structures of reality.

9. References

1. Rukhin, A., Soto, J., Nechvatal, J., Smid, M., Barker, E., Leigh, S., Levenson, M., Vangel, M., Banks, D., Heckert, A., Dray, J., & Vo, S. (2010).
   A Statistical Test Suite for Random and Pseudorandom Number Generators for Cryptographic Applications.
   NIST Special Publication 800-22, Revision 1a.
   National Institute of Standards and Technology (NIST).
   https://doi.org/10.6028/NIST.SP.800-22r1a

2. Herrero-Collantes, M., & Garcia-Escartin, J. C. (2017).
   Quantum Random Number Generators.
   Reviews of Modern Physics, 89(1), 015004.
   https://doi.org/10.1103/RevModPhys.89.015004

3. Ma, X., Yuan, X., Cao, Z., Qi, B., & Zhang, Z. (2016).
   Quantum Random Number Generation.
   npj Quantum Information, 2, 16021.
   https://doi.org/10.1038/npjqi.2016.21

4. Wilson, C. M., Johansson, G., Pourkabirian, A., Simoen, M., Johansson, J. R., Duty, T., Nori, F., & Delsing, P. (2011).
   Observation of the Dynamical Casimir Effect in a Superconducting Circuit.
   Nature, 479(7373), 376–379.
   https://doi.org/10.1038/nature10561

5. Unruh, W. G. (1976).
   Notes on Black Hole Evaporation.
   Physical Review D, 14(4), 870–892.
   https://doi.org/10.1103/PhysRevD.14.870

6. Misner, C. W., Thorne, K. S., & Wheeler, J. A. (1973).
   Gravitation.
   W.H. Freeman and Company.

7. Ng, Y. J., & van Dam, H. (1994).
   Limit to Spacetime Measurement.
   Modern Physics Letters A, 9(4), 335–340.
   https://doi.org/10.1142/S0217732394000356

8. Mallat, S. (2009).
   A Wavelet Tour of Signal Processing (Third Edition).
   Academic Press.

9. Cover, T. M., & Thomas, J. A. (2006).
   Elements of Information Theory (Second Edition).
   Wiley-Interscience.

10. Chandola, V., Banerjee, A., & Kumar, V. (2009).
    Anomaly Detection: A Survey.
    ACM Computing Surveys, 41(3), Article 15.
    https://doi.org/10.1145/1541880.1541882

11. Youvan, D. C. (2025).
    Epistemic Jump Computing: A New Paradigm for Informational Phase Transitions in Quantum Systems.
    DOI: 10.13140/RG.2.2.35425.01123

12. Youvan, D. C. (2025).
    Quantum Epistemic Jumps: Modeling Informational Phase Transitions Through Hamiltonian Restructuring.
    DOI: 10.13140/RG.2.2.14663.20644


REAL-TIME AND DEEP-TIME
DETECTION OF QUANTUM FOAM ANOMALIES
IN QUANTUM RANDOM NUMBER GENERATOR OUTPUTS